

This drawing is an integral part of the general statement of use and technical manual

Item	Part number	Q-ty	Title	Material
1	16-4-1200	1	Body of Pressure Vessel	Glass/Epoxy
2	044-405-1201	2	Side port 4"	Super duplex stainless steel
3	285772409	4	Retaining ring	Stainless steel
4	006-406-1205	2	Disk for port	Stainless steel
5	014-400-0709	2	Seal for port	EPDM
6	005-661-1200	2	Support ring	Aluminum
7	003-165-1200	2	Base plate	Aluminum
8	007-402-0084	2	Seal for s.plate	EPDM
9	013-165-1200	2	Sealing plate	Engineering plastic
10	011-420-1202	2	Retaining ring	Stainless steel
11	007-112-0053	2	Seal for p.port	EPDM
12	008-160-1204	2	Permeate port 3"	Engineering plastic
13	004-165-1041	1	Thrust ring	Engineering plastic
14	007-085-0053	2	Seal for adapter	EPDM
15	As required	2	Adapter	Engineering plastic
16	As required	2	Membrane seal	EPDM
17	010-160-9001	3	Spacer 1mm.	Engineering plastic
18	010-160-9005	2-8	Spacer 5mm.	Engineering plastic
19	016-002-0845	8	Socket screw	Stainless steel
20	015-160-0000	2	Strap assy.	Stainless steel
21	012-160-0000	2-3	Saddle	Engineering plastic
22				
23				
24				

Shell length code	L (l.o.a.), mm. / inch	P, port to port mm. / inch	M, length for membrane elements, mm. / inch	S # (span) mm. / inch	W weight kg. / lb.
1	2303	1407	1107	700	401
	90.67	55.39	43.6	27.6	884
2	3335	2439	2139	1700	465
	131.30	96.02	84.2	66.9	1025
3	4367	3471	3171	2700	529
	171.93	136.65	124.8	106.3	1166
4	5399	4503	4203	3420	593
	212.56	177.28	165.5	134.6	1307
5	6431	5535	5235	4450	656
	253.19	217.91	206.1	175.2	1448
6	7463	6567	6267	5470	720
	293.82	258.54	246.7	215.4	1588
7	8495	7599	7299	6500	784
	334.45	299.17	287.4	255.9	1729
8	9527	8631	8331	7530	848
	375.08	339.80	328	296.5	1870

Notes:

- All dimensions are for reference only, not for construction unless certified. Dimensions L, P, M can be varied according to exact membrane type.
- Item 17 & 18 should be located on feed side for membranes shimming.
- Item 13 downstream only.
- Item 19 - closing torque not to exceed 2 Nm.
- Drawing unit: mm. (inches).
- Saddles can be shimmed if required.
- The vessel is supplied with two straps for external saddles.
- Do not scale drawing, may be reprinted on any paper size or copied.
- Vessel's ports diameters according to ANSI Standards.

Warning:

- Never pressurize a pressure vessel that was not loaded with membrane elements.
- Wrong manifolding may cause an excessive pressure on port what can lead to leaks.
- Max. allowable working pressure not to exceed 1200 psi. (83 bar).
- Permeate internal pressure not to exceed 125 psi. (8.6 bar).
- Operating temperature not to exceed 65°C (150°F).

	TITLE:	BEL16-S-1200 psi. RO PRESSURE VESSEL	DESIGN	DMG	04/05/2020
	CHECK	JME	04/05/2020		
	DRAWING NO:	BEL16-S4-1200	APPR.	MAF	04/05/2020
THIS DRAWING IS PROPERTY OF BEL GROUP LIMITED IT IS STRICTLY FORBIDDEN TO USE, COPY, REPRODUCE OR DISCLOSE ANY PART OF IT TO THIRD PARTY WITHOUT WRITTEN AUTHORIZATION.					
					REV.: 1



ORDER / R.F.Q. FORM - 16" SIDE PORT PRESSURE VESSELS
Please fill and send it to your contact at BEL


P.O. / R.F.Q. Number:

Customer name:

1. NEW SYSTEM EXISTING SYSTEM or Replacement Please provide details:

2. F/C PORTS CONFIGURATION: Please indicate side port requirement on each side of the vessel
(Mark the letter indicating port diameter in the box at each required port location, only in 180° on the same side)

A – 4" *Vessel's Port diameters, according to ANSI Standards.*



3. NUMBER OF VESSELS: Units
(Please, use separate forms for each type in case of multi-type orders)

4. WORKING PRESSURE RATE (PSI): 300 450 600 1,000 1,200

5. NUMBER OF MEMBRANE ELEMENTS IN EACH VESSEL: (1,,,,,,8)

6. MEMBRANE BRAND AND TYPE:

7. CONFIRM TYPE: BEL16-S - (x) - - M
of ports dia. of port pressure # of membranes - *(Example: BEL8 - S(4 x 2.5") – 1,000 - 7M)*

8. PERMEATE PORTS OUTLET: 3" NPT male 3" Victaulic grooved

9. ASME code SEC. X, RP stamped vessel: NO YES
(Please, contact for pricing)

10. COLOR: Standard (white, RAL 9010) Other RAL number:
(Please, contact for pricing)

Customer signature:

Date:

FOR DETAILS, PLEASE, VISIT OUR WEBSITE: www.belvessels.com