




Shell length code	L (l.o.a.) mm. inch	P (port to port) mm. inch	S # (span) mm. inch	M, mm/in length for membranes elements	W weight kg. lb.	Article number
21	799	540	180	485	9	401201-21
	31,5	21,3	7,09	19,1	20	
22	1332,5	1073,5	650	1018,5	13	401201-22
	52,5	42,3	25,59	40,1	29	
23	1866	1607	1200	1552	18	401201-23
	73,5	63,3	47,24	61,1	40	
24	2399,5	2140,5	1700	2085,5	23	401201-24
	94,5	84,3	66,93	82,1	51	
25	2934	2675	2200	2620	27	401201-25
	115,5	105,3	86,61	103,1	60	
26	3467,5	3208,5	2700	3153,5	32	401201-26
	136,5	126,3	106,30	124,2	71	
27	4002,5	3743,5	3200	3688,5	37	401201-27
	157,6	147,4	125,98	145,2	82	
28	4537	4278	3700	4223	41	401201-28
	178,6	168,4	145,67	166,3	90	
29	5072	4813	4200	4758	46	401201-29
	199,7	189,5	165,35	187,3	101	
30	5606,5	5347,5	4700	5292,5	50	401201-30
	220,7	210,5	185,04	208,4	110	
31	6142	5883	5200	5828	55	401201-31
	241,8	231,6	204,72	229,4	121	
32	6675,5	6416,5	5700	6361,5	60	401201-32
	262,8	252,6	224,41	250,5	132	

Table №1 for membrane length 21" (533.4mm.).
Table №2 for membrane length 40" (1016mm.).

Shell length code	L (l.o.a.) mm. inch	P port to port, mm. Inch	S # (span) mm. inch	M, mm/in length for membranes elements (with membrane type)		W weight kg. lb.	Article number
1	1284	1024	620	1020	970	13	411200-1
	50,6	40,3	24	40,2	38,2	29	
2	2300	2040	1550	2036	1986	22	411200-2
	90,6	80,3	61	80,2	78,2	49	
3	3316	3056	2550	3052	3002	31	411200-3
	130,6	120,3	100	120,2	118,2	68	
4	4332	4072	3250	4068	4018	39	411200-4
	170,6	160,3	128	160,2	158,2	86	
5	5349	5089	4250	5085	5035	48	411200-5
	210,6	200,4	167	200,2	198,2	106	
6	6367	6107	5250	6103	6053	57	411200-6
	250,7	240,4	207	240,3	238,3	126	

Warning.

1. Never pressurize a pressure vessel that was not loaded with membrane elements.
2. Wrong manifolding may cause an excessive pressure on port what can lead to leaks.
3. Max. allowable working pressure not to exceed 1200 psi. (83 bar).
4. Permeate internal pressure not to exceed 125 psi. (8.6 bar).
5. Operating temperature not to exceed 65°C (150°F).

Item	Part Number	Q-ty	Description	Material
1	411200-0	1	Body of Pressure Vessel	Glass/Epoxy
2	009-107-1200	2	Sideport 1"	Super Duplex Stainless steel
3	006-116-1202	2	Disk for Sideport 1"	Stainless steel
4	014-100-0505	2	Seal for Sideport 1"	EPDM
5	011-100-1202	4	R.Ring for Sideport 1"	Stainless steel
6	005-461-1200	2	Support Ring	Aluminium
7	011-401-1202	2	Retaining ring for S.Ring	316 Stainless steel
8	008-400-1215	2	Permeate tube	Engineering plastic
9	55412369	2	R.Ring for permeate tube	316 Stainless steel
10	003-420-1215	2	Base plate	Aluminium
11	003-400-0005	2	Sealing plate	Engineering plastic
12	55412360	2	Seal for sealing plate	EPDM
13	55412367	2	Seal for adapter	EPDM
14	55412377	0-6	Disk spacer	Engineering plastic
15	as required	2	Membrane seal	EPDM
16	as required	2	Membrane Adapter	Engineering plastic

Vessel support parts - optional -

17*	55410352	2-3	Saddle	Engineering plastic
18*	55410246	2	Strap	Stainless steel

	BEL4-S(1")-1200 psi. RO PRESSURE VESSEL	DESIGN	VMLS	29/08/2025
		CHECK	SRS	29/08/2025
	DRAWING NO: BEL4-S(1")-1200		APPR.	VMLS
THIS DRAWING IS PROPERTY OF BEL GROUP LIMITED IT IS STRICTLY FORBIDDEN TO USE, COPY, REPRODUCE OR DISCLOSE ANY PART OF IT TO THIRD PARTY WITHOUT WRITTEN AUTHORIZATION.				
				REV.: 6

ORDER / R.F.Q. FORM - 4" SIDE PORT PRESSURE VESSELS

Please fill and send it to your contact at BEL

P.O. / R.F.Q. Number:


Customer name:

1. F/C PORTS CONFIGURATION: Please indicate side port requirement on each side of the vessel
(Mark the letter indicating port diameter in the box at each required port location)

A – 1" Victaulic B – 1.5" Victaulic (Except for 1500 psi models)

Vessel's Port diameters, according to ANSI Standards.

(Ports with a diameter of 1.5" cannot be mounted in 90° with any other port)



General Information for Permeate ports:

- Vessels 300 psi & 450 psi: ½" NPT Female.
- Vessels 600 psi up to 1500 psi: ½" NPT Male.

2. NUMBER OF VESSELS:

(Please use separate forms for each type in case of multi-type orders)

3. WORKING PRESSURE RATE (PSI): 300 / 450 / 600 / 1,000 / 1,200 / 1500

4. NUMBER OF MEMBRANE ELEMENTS IN EACH VESSEL:

For 40" membranes length: (1 to 6)

For 21" membranes length: (1 to 12)

5. MEMBRANE BRAND AND TYPE:

6. CONFIRM TYPE – BEL4-S- (x) - - M

of ports diam. Port pressure #membranes

7. SADDLES & STRAPS (Optional): NO / YES *(please contact for pricing)*

8. ADAPTERS OPTIONS: Two Standard adapters / Standard & Solid (blind) adapter

9. COLOR: Standard (white, RAL 9010) / Other RAL number: *(contact for pricing)*

Customer signature:

Date:

FOR DETAILS PLEASE VISIT OUR WEBSITE: www.belvessels.com